

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/65 R 24
LI/SS	140 D/143 A8

Dimensions US Standard

Usa code	94028528
Section Width (inch)	18.9
Overall Diameter (inch)	48.6
Static Loaded Radius (inch)	22.1
Rolling Circumference (inch)	146.9
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E4-106R-000617
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2650	3090	3470	3860	4240	4570	5070	5510
30	2780	3240	3650	4060	4460	4810	5320	5790
25	2890	3370	3790	4210	4630	4990	5530	6010
20	3040	3550	4000	4440	4880	5270	5830	6340
5 LT	3550	4140	4660	5170	5690	6140	6800	7390
5 HT	3040	3550	4000	4440	4880	5270	5830	6340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..