

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steelbelted technology.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	220/70 R 16
LI/SS	99 A8/B

Dimensions US Standard

Usa code	94045365
Section Width (inch)	8.7
Overall Diameter (inch)	28.1
Static Loaded Radius (inch)	12.8
Rolling Circumference (inch)	84.4
Rim Rec	W 7
Rim Alt	W 8
ECE	E11-106R-003354
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	800	930	1070	1200	1330	1480	1600	1710
25	800	930	1070	1200	1330	1480	1600	1710
20	870	990	1140	1290	1430	1580	1710	1830
5 LT	1080	1250	1420	1610	1800	1970	2140	2290
5 HT	870	990	1140	1290	1430	1580	1710	1830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 19:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..