

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/70 R 24
LI/SS	138 D

Dimensions US Standard

Usa code	94062195
Section Width (inch)	18.9
Overall Diameter (inch)	51.8
Static Loaded Radius (inch)	22.8
Rolling Circumference (inch)	153.3
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005519
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	2870	3340	3800	4280	4740	5200
30	3010	3510	4000	4490	4980	5470
25	3140	3650	4170	4670	5190	5700
20	3300	3840	4380	4920	5460	5990
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3300	3840	4380	4920	5460	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 16:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..