

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STEEL BELTED
Type	TL
Tyre Size	480/80 R 50 (18.4 R 50)
LI/SS	176 A8

Dimensions US Standard

Usa code	94045358
Section Width (inch)	19.3
Overall Diameter (inch)	80.2
Static Loaded Radius (inch)	37.2
Rolling Circumference (inch)	243.4
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; W 15 L
ECE	E4-106R-001495
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52	58	64	73
30	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
25	4540	5210	5990	6760	7530	8300	8970	9640	10490	11430	12060	12840	13930	15650
20	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750
5 LT	6080	6990	8020	9060	10090	11120	12030	12930	14060	15320	16160	17210	18670	20980
5 HT	4860	5580	6400	7230	8060	8880	9610	10330	11230	12230	12910	13750	14910	16750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..