

AGRIMAX RT 855 - Data Sheet



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

SIZE	Version	TRA Code	LI/SS	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
180/95 R 16 (6.50 R 16)	STANDARD	R1W	105 A8/B		5.5 F	6.0 F	185	760	340	2265	360	TL		E4-106R-000756
210/95 R 16 (7.50 R 16)	IMPLEMENT	R1W	116A8	116 A8	W 7	W 6 ; 6 LB	214	806	350	2353	380	TL		E11-106R-006625
210/95 R 16 (7.50 R 16)	STANDARD	R1W	106 A8/B		W 7	W 6 ; 6 LB	214	806	360	2387	380	TL		E4-106R-000608
210/95 R 18 (7.50 R 18)	IMPLEMENT	R1W		122 A8	W 7	W 6	214	855	378	2565	410	TL		E11-106R-007207
210/95 R 18 (7.50 R 18)	STANDARD	R1W	108 A8/B		W 7	W 6	214	855	385	2565	410	TL		E4-106R-00634
250/80 R 18	STANDARD	R1W	125 A8/125 B		W 8	W 7 ; W 9	250	835	375	2539	410	TL		E11-106R-006605
210/90 R 20 (8.3 R 20)	STANDARD	R1W	110 A8/B		W 7	W 6	211	890	412	2681	450	TL		E4-106R-001817
210/95 R 20 (7.50 R 20)	STANDARD	R1W	110 A8/B		W 7	W 6	214	908	418	2749	450	TL		E4-106R-000637
250/85 R 20 (9.5 R 20)	STANDARD	R1W	116 A8/B		W 8	W 7 ; W 9	250	940	424	2812	450	TL		E4-106R-000639
280/85 R 20 (11.2 R 20)	STANDARD	R1W	122 A8/B		W 10	W 9	292	984	447	2977	475	TL		E11-106R-007936
280/85 R 20 (11.2 R 20)	STANDARD	R1W	112 A8/B		W 10	W 9	292	984	441	2952	475	TL		E4-106R-000642
320/85 R 20 (12.4 R 20)	STANDARD	R1W	119 A8/B		W 11	W 9 ; W 10	329	1052	467	3100	500	TL		E4-106R-000645
250/85 R 22	SPECIAL	R1W	113 A8/B		W 8	W 7	251	985	453	2964	475	TL	1	E11-106R-002973
250/85 R 22 (9.5 R 22)	STANDARD	R1W	113 A8/B		W 8	W 7	251	985	453	2964	475	TL		E11-106R-002973
250/85 R 24 (9.5 R 24)	SPECIAL	R1W	109 A8/B		W 8	W 7 ; W 9	251	1036	475	3104	500	TL		E4-106R-000638
250/85 R 24 (9.5 R 24)	STANDARD	R1W	109 A8/B		W 8	W 7 ; W 9	251	1036	475	3104	500	TL		E4-106R-000638
280/85 R 24 (11.2 R 24)	SPECIAL	R1W	115 A8/B		W 10	W 9	292	1086	492	3224	525	TL		E4-106R-000611
280/85 R 24 (11.2 R 24)	STANDARD	R1W	115 A8/B		W 10	W 9	292	1086	492	3224	525	TL		E4-106R-000611
320/85	SPECIAL	R1W	122		W 11	W 9 ; W 10	329	1154	519	3424	550	TL		E4-

R 24 (12.4 R 24)			A8/B										106R-000613
320/85 R 24 (12.4 R 24)	STANDARD	R1W	122 A8/B		W 11	W 9 ; W 10	329	1154	519	3424	550	TL	E4-106R-000613
340/85 R 24 (13.6 R 24)	SPECIAL	R1W	125 A8/B		W 12	W 11	353	1188	531	3540	575	TL	E4-106R-000604
340/85 R 24 (13.6 R 24)	STANDARD	R1W	125 A8/B		W 12	W 11	353	1188	531	3540	575	TL	E4-106R-000604
380/85 R 24 (14.9 R 24)	SPECIAL	R1W	131 A8/B		W 12	W 11 ; W 13	380	1256	554	3720	600	TL	E4-106R-000592
380/85 R 24 (14.9 R 24)	STANDARD	R1W	131 A8/B		W 12	W 11 ; W 13	380	1256	554	3720	600	TL	E4-106R-000592
420/85 R 24 (16.9 R 24)	SPECIAL	R1W	137 A8/B		W 15 L	W 14 L ; W 13	450	1324	582	3900	625	TL	E4-106R-000595
420/85 R 24 (16.9 R 24)	STANDARD	R1W	137 A8/B		W 15 L	W 14 L ; W 13	450	1324	582	3900	625	TL	E4-106R-000595
250/85 R 28 (9.5 R 28)	SPECIAL	R1W	112 A8/B		W 8	W 7 ; W 9	251	1137	519	3421	550	TL	E4-106R-000646
250/85 R 28 (9.5 R 28)	STANDARD	R1W	112 A8/B		W 8	W 7 ; W 9	251	1137	519	3421	550	TL	E4-106R-000646
280/85 R 28 (11.2 R 28)	SPECIAL	R1W	118 A8/B		W 10	W 9	292	1187	545	3558	575	TL	E4-106R-000614
280/85 R 28 (11.2 R 28)	STANDARD	R1W	118 A8/B		W 10	W 9	292	1187	545	3558	575	TL	E4-106R-000614
320/85 R 28 (12.4 R 28)	SPECIAL	R1W	124 A8/B		W 11	W 9 ; W 10	329	1255	569	3743	600	TL	E4-106R-000615
320/85 R 28 (12.4 R 28)	STANDARD	R1W	124 A8/B		W 11	W 9 ; W 10	329	1255	569	3743	600	TL	E4-106R-000615
340/85 R 28 (13.6 R 28)	SPECIAL	R1W	127 A8/B		W 12	W 11	353	1289	588	3890	625	TL	E4-106R-000593
340/85 R 28 (13.6 R 28)	STANDARD	R1W	139 A8/B		W 12	W 11	353	1315	603	3963	625	TL	E11-106R-008233
340/85 R 28 (13.6 R 28)	STANDARD	R1W	127 A8/B		W 12	W 11	353	1289	588	3890	625	TL	E4-106R-000593
380/85 R 28 (14.9 R 28)	SPECIAL	R1W	133 A8/B		W 12	W 11 ; W 13	380	1357	606	4015	650	TL	E4-106R-000597
380/85 R 28 (14.9 R 28)	STANDARD	R1W	133 A8/B		W 12	W 11 ; W 13	380	1357	606	4015	650	TL	E4-106R-000597
420/85 R 28 (16.9 R	SPECIAL	R1W	139 A8/B		W 15 L	W 13 ; W 14 L	438	1425	638	4241	675	TL	E4-106R-000602

28)												
420/85 R 28 (16.9 R 28)	STANDARD	R1W	139 A8/B	W 15 L	W 13 ; W 14 L	438	1425	638	4241	675	TL	E4- 106R- 000602
380/85 R 30 (14.9 R 30)	SPECIAL	R1W	135 A8/B	W 12	W 11 ; W 13	380	1408	633	4190	675	TL	E4- 106R- 000594
380/85 R 30 (14.9 R 30)	STANDARD	R1W	135 A8/B	W 12	W 11 ; W 13	380	1408	633	4190	675	TL	E4- 106R- 000594
420/85 R 30 (16.9 R 30)	SPECIAL	R1W	140 A8/B	W 15 L	W 13 ; W 14 L	438	1475	661	4421	700	TL	E4- 106R- 000654
420/85 R 30 (16.9 R 30)	STANDARD	R1W	140 A8/B	W 15 L	W 13 ; W 14 L	438	1475	661	4421	700	TL	E4- 106R- 000654
460/85 R 30 (18.4 R 30)	SPECIAL	R1W	145 A8/B	W 16 L	W 14 L ; W 15 L	475	1544	680	4562	725	TL	E4- 106R- 000774
460/85 R 30 (18.4 R 30)	STANDARD	R1W	145 A8/B	W 16 L	W 14 L ; W 15 L	475	1544	680	4562	725	TL	E4- 106R- 000774
320/85 R 32 (12.4 R 32)	SPECIAL	R1W	126 A8/B	W 11	W 9 ; W 10	329	1357	621	4081	650	TL	E4- 106R- 000758
320/85 R 32 (12.4 R 32)	STANDARD	R1W	126 A8/B	W 11	W 9 ; W 10	329	1357	621	4081	650	TL	E4- 106R- 000758
320/85 R 34 (12.4 R 34)	SPECIAL	R1W	141 A8/B	W 11	W 9 ; W 10	329	1408	645	4280	675	TL	E4- 106R- 000758
320/85 R 34 (12.4 R 34)	STANDARD	R1W	141 A8/B	W 11	W 9 ; W 10	329	1408	645	4280	675	TL	E4- 106R- 001395
380/85 R 34 (14.9 R 34)	SPECIAL	R1W	137 A8/B	W 12	W 11 ; W 13	380	1509	682	4504	725	TL	E4- 106R- 000655
380/85 R 34 (14.9 R 34)	STANDARD	R1W	137 A8/B	W 12	W 11 ; W 13	380	1509	682	4504	725	TL	E4- 106R- 000655
420/85 R 34 (16.9 R 34)	SPECIAL	R1W	142 A8/B	W 15 L	W 13 ; W 14 L	438	1578	709	4702	750	TL	E4- 106R- 000656
420/85 R 34 (16.9 R 34)	STANDARD	R1W	142 A8/B	W 15 L	W 13 ; W 14 L	438	1578	709	4702	750	TL	E4- 106R- 000656
420/85 R 34 (16.9 R 34)	STANDARD	R1W	147 A8/B	W 15 L	W 13 ; W 14 L	438	1578	728	4782	750	TL	E11- 106R- 005179
460/85 R 34 (18.4 R 34)	SPECIAL	R1W	147 A8/B	W 16 L	W 14 L ; W 15 L	475	1646	721	4865	775	TL	E4- 106R- 000632
460/85 R 34 (18.4 R 34)	STANDARD	R1W	147 A8/B	W 16 L	W 14 L ; W 15 L	475	1646	721	4865	775	TL	E4- 106R- 000632
460/85 R 34 (18.4 R 34)	STANDARD	R1W	158 A8/B	W 16 L	W 14 L ; W 15 L	475	1646	721	4865	775	TL	E11- 106R- 006759

320/85 R 36 (12.4 R 36)	SPECIAL	R1W	128 A8/B		W 11	W 9 ; W 10	329	1458	672	4404	700	TL		E4- 106R- 000762
320/85 R 36 (12.4 R 36)	STANDARD	R1W	128 A8/B		W 11	W 9 ; W 10	329	1458	672	4404	700	TL		E4- 106R- 000762
320/85 R 36	STANDARD	R1W	147 D/150 A8		W 11	W 9 ; W 10	329	1458	672	4404	700	TL		E11- 106R- 003511
340/85 R 36 (13.6 R 36)	SPECIAL	R1W	132 A8/B		W 12	W 11	353	1492	689	4507	725	TL		E4- 106R- 000763
340/85 R 36 (13.6 R 36)	STANDARD	R1W	132 A8/B		W 12	W 11	353	1492	689	4507	725	TL		E4- 106R- 000763
320/85 R 38 (12.4 R 38)	SPECIAL	R1W	143 A8/B		W 11	W 9 ; W 10 ; DW 10	329	1509	700	4580	725	TL		E4- 106R- 000781
320/85 R 38 (12.4 R 38)	STANDARD	R1W	143 A8/B		W 11	W 9 ; W 10 ; DW 10 ; DW11	329	1509	700	4580	725	TL		E4- 106R- 000781
340/85 R 38 (13.6 R 38)	SPECIAL	R1W	133 A8/B		W 12	W 11	353	1543	712	4668	750	TL		E4- 106R- 000766
340/85 R 38 (13.6 R 38)	STANDARD	R1W	133 A8/B		W 12	W 11	353	1543	712	4668	750	TL		E4- 106R- 000766
380/85 R 38 (14.9 R 38)	SPECIAL	R1W	139 A8/B		W 12	W 11 ; W 13	380	1611	736	4842	775	TL		E4- 106R- 000660
380/85 R 38 (14.9 R 38)	STANDARD	R1W	139 A8/B		W 12	W 11 ; W 13	380	1611	736	4842	775	TL		E4- 106R- 000660
420/85 R 38 (16.9 R 38)	SPECIAL	R1W	144 A8/B		W 15 L	W 13 ; W 14 L	438	1679	763	5014	800	TL		E4- 106R- 000661
420/85 R 38 (16.9 R 38)	STANDARD	R1W	144 A8/B		W 15 L	W 13 ; W 14 L	438	1679	763	5014	800	TL		E4- 106R- 000661
460/85 R 38 (18.4 R 38)	SPECIAL	R1W	149 A8/B		W 16 L	W 14 L ; W 15 L	475	1747	785	5205	825	TL		E4- 106R- 000618
460/85 R 38 (18.4 R 38)	STANDARD	R1W	149 A8/B		W 16 L	W 14 L ; W 15 L	475	1747	785	5205	825	TL		E4- 106R- 000618
480/80 R 38 (18.4 R 38)	STANDARD	R1W	149 A8/B		DW 16 L	W 14 L ; W 15 L	475	1747	785	5161	825	TL		E4- 106R- 001822
520/85 R 38 (20.8 R 38)	SPECIAL	R1W	155 A8/B		DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5466	875	TL		E4- 106R- 000601
520/85 R 38	SPECIAL	R1W	170 A8/B		DW 16 L	DW 18 L ; DD 16 L	516	1849	847	5595	875	TL	1	E4- 106R- 001411
520/85 R 38 (20.8 R 38)	STANDARD	R1W	155 A8/B		DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5466	875	TL		E4- 106R- 000601
520/85 R 38 (20.8 R 38)	STANDARD	R1W	170 A8/B		DW 16 L	DW 18 L ; DD 16 L	516	1849	847	5595	875	TL		E4- 106R- 001411

480/80 R 42 (18.4 R 42)	STANDARD	R1W	151 A8/B	W 16 A ; DD 16 ; DW 16 A	DD 16 L ; DW 16 L ; W 16 L	479	1835	835	5495	875	TL	E4- 106R- 000791	
520/85 R 42 (20.8 R 42)	SPECIAL	R1W	157 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	TL	E4- 106R- 000792	
520/85 R 42 (20.8 R 42)	SPECIAL	R1W	167 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	TL	E4- 106R- 001491	
520/85 R 42 (20.8 R 42)	STANDARD	R1W	157 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	TL	E4- 106R- 000792	
520/85 R 42 (20.8 R 42)	STANDARD	R1W	167 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	TL	E4- 106R- 001491	
420/80 R 46 (16.9 R 46)	SPECIAL	R1W	159 D/170 A2	W 13	W 12	418	1840	863	5641	900	TL	1	E4- 106R- 001489
420/80 R 46 (16.9 R 46)	STANDARD	R1W	151 D/162 A2	W 13	W 12	418	1840	863	5641	900	TL	E4- 106R- 001730	
420/80 R 46 (16.9 R 46)	STANDARD	R1W	159 D/170 A2	W 13	W 12	418	1840	863	5641	900	TL	E4- 106R- 001489	
480/80 R 46 (18.4 R 46)	STANDARD	R1W	158 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	TL	E4- 106R- 001731	
480/80 R 46 (18.4 R 46)	STANDARD	R1W	164 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	TL	E4- 106R- 000798	
520/85 R 46	SPECIAL	R1W	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	930	6157	975	TL	1	E4- 106R- 001415
520/85 R 46 (20.8 R 46)	STANDARD	R1W	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	930	6157	975	TL	E4- 106R- 001415	
520/85 R 46 (20.8 R 46)	STANDARD	R1W	173 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2075	964	6310	975	TL	E4- 106R- 001494	
420/80 R 50 (16.9 R 50)	STEEL BELTED	R1W	165 A8/B	W 13	W 12	418	1951	915	5955	950	TL	E11- 106R- 0010078	
480/80 R 50 (18.4 R 50)	STANDARD	R1W	159 A8/B	DW 16 L	DW 15 L ; W 15 L	489	2036	941	6183	975	TL	E4- 106R- 001486	
480/80 R 50 (18.4 R 50)	STEEL BELTED	R1W	176 A8	DW 16 L	DW 15 L ; W 15 L	489	2036	945	6183	975	TL	E4- 106R- 001495	
520/85 R 50 (20.8 R 50)	STANDARD	R1W	165 A8/B	DW 16L	DW 18 L	516	2154	992	6472	1025	TL	E11- 106R- 004895	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..