

AGRIMAX RT 945 - Data Sheet



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Tractor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
420/90 R 30	STANDARD	R1W	147 A8/B	DW13	W 14 L	418	1518	684	4571	700	TL	E11-106R-006021
320/90 R 42 (12.4 R 42)	STANDARD	R1W	139 A8/B	W 10	W 9 ; W 11	319	1643	760	4944	775	TL	E4-106R-000783
320/90 R 46 (12.4 R 46)	STANDARD	R1W	146 A8/B	W 10	W 9 ; W 11	319	1744	810	5232	825	TL	E4-106R-001399
320/90 R 46 (12.4 R 46)	STANDARD	R1W	148 D/151 A8	W 10	W 9 ; W 11	319	1744	810	5232	825	TL	E11-106R-004068
380/90 R 46 (14.9 R 46)	STANDARD	R1W	155 A8/B	W 12	W 11 ; W 13	380	1852	866	5648	875	TL	E4-106R-00797
380/90 R 46 (14.9 R 46)	STANDARD	R1W	159 A8/B	W 12	W 11 ; W 13	380	1852	859	5699	875	TL	E4-106R-001409
320/90 R 50 (12.4 R 50)	STANDARD	R1W	150 A8/B	W 10	W 9 ; W 11	319	1846	873	5618	875	TL	E4-106R-000787
380/90 R 50 (14.9 R 50)	STANDARD	R1W	151 A8/B	W 12	W 11 ; W 13	380	1954	906	5900	925	TL	E4-106R-001487
380/90 R 50 (14.9 R 50)	STANDARD	R1W	160A8/B	W 12	W 11 ; W 13	390	1954	921	5958	925	TL	E11-106R-006446
320/90 R 54 (12.4 R 54)	STANDARD	R1W	156 A8/B	W 10	W 9 ; W 11	319	1948	930	6021	925	TL	E11-106R-003474
380/90 R 54 (14.9 R 54)	STANDARD	R1W	158 A8/B	W 12	W 11 ; W 13	380	2056	962	6232	975	TL	E4-106R-001488

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 17:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..