

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	230/95 R 44 (9.5 R 44)
LI/SS	134 A8/B

Dimensions International Standard

Section Width (mm)	228
Overall Diameter (mm)	1556
Static Loaded Radius (mm)	739
Rolling Circumference (mm)	4788
SRI (mm)	750
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000777
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	830	1085	1315	1445	1530	1675	1825	1975	2120	-
40	830	1085	1315	1445	1530	1675	1825	1975	2120	-
30	890	1160	1410	1545	1635	1795	1955	2115	2270	-
10	990	1245	1530	1815	2100	2165	2420	2675	2930	3180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 01:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..