

## AGRIMAXFACTOR - Technical Specifications



### Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	620/70 R 46
LI/SS	162D/165A8

# Dimensions US Standard

Usa code	94076451
Section Width (inch)	24.6
Overall Diameter (inch)	80.2
Static Loaded Radius (inch)	35.9
Rolling Circumference (inch)	239.2
Rim Rec	DW 20 B
ECE	E11-106R-0010339
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	5760	6700	7650	8590	9530	10470
30	6050	7040	8040	9030	10020	11000
25	6320	7350	8380	9410	10450	11470
15	6640	7720	8800	9890	10970	12050
5 LT	7730	8980	10250	11510	12780	14030
5 HT	6640	7720	8800	9890	10970	12050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 17:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..