

## ARROW - Technical Specifications



### Description

ARROW is suitable for transport applications with trailers. It is a road-oriented tire that provides a better mileage and a longer service life. ARROW has a high load capacity also at high speeds. An HD version made of a special compound is also available for users that require advanced performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 20

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	270
Overall Diameter (mm)	1040
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

## Load capacity (Kg)

km/h / bar	7.25
40	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..