

## AS 504 - Technical Specifications



### Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TT
Tyre Size	7.50 - 20
LI/SS DRIVE WHEEL	103 A8
LI/SS FREE ROLLING	116 A8

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	209
Overall Diameter (mm)	904
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2695
SRI (mm)	425
Rim Rec	5.50 F
Rim Alt	4.50 E ; 6.00 F ; 5.00 F
ECE	E4-106R-002636

## Load capacity (Kg)

km/h / bar	3.20
10 FR	1750
25 FR	1490
30 FR	1400
40 FR	1250
10 DW	1225
25 DW	1040
30 DW	980
40 DW	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 23:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..