

AT 111 HD - Data Sheet



Description

AT 111 HD is suitable for all-terrain sport racing with ATVs. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: ATV

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 20 X 11 - 9	STANDARD	94026883	43 J	6	9.0 AT	8.5 AT	10.8	20.3	TL	E4-75R-0006326
AT 22 X 11 - 9	STANDARD	94026890		6	9.0 AT	8.5 AT	11	22	TL	E4-75R-0006332
AT 20 X 11 - 10	STANDARD	94027002		6	9.0 AT	8.5 AT	11	19.9	TL	E4-75R-0006327
AT 21 X 7 - 10	STANDARD	94027019	30 J	6	5.5 AT	6.0 AT	7	21	TL	E4-75R-0006329
AT 22 X 11 - 10	STANDARD	94027026		6	9.0 AT	8.5 AT	11	22	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD	94027033		6	5.5 AT	6.0 AT	6.9	22	TL	E4-75R-0006331
AT 23 X 7 - 10	STANDARD	94027040		6	5.5 AT	6.0 AT	6.9	23	TL	E4-75R-0006335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 19:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..