

## AT 603 - Technical Specifications



### Description

AT 603 is a bias agro-industrial tire for implement machinery and backhoe loaders. AT 603 has been engineered to ensure great durability and traction on drive wheels providing best performance on every surface as well as excellent self-cleaning properties. The AT 603 "special" version has a reinforced casing, while the "HD" version offers improved cut and chip resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Backhoe Loader • Implement Machinery  
Industrial: Backhoe Loader

Version	STANDARD
Type	TL
Tyre Size	15.5 - 25

## Dimensions US Standard

Usa code	94059775
Ply Rating	12
Section Width (inch)	16.1
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	152
Rim Rec	12.00/1.3
Rim Alt	12.00/1.3 (DC)
TRA Code	E2/G2/L2

## Load capacity (lbs)

mph / psi	36	58	36
30	7160	-	-
5	-	12350	-
25	-	-	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 15:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..