

AW 09 - Technical Specifications



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	125 A8
LI/SS FREE ROLLING	138 A8

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2491
Rim Rec	13.00
ECE	E4-106R-000379

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	3305
	25 FR	2810
	30 FR	2645
	40 FR	2360
	10 DW	2310
	25 DW	1965
	30 DW	1850
	40 DW	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 16:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..