

AW 705 - Technical Specifications



Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS FREE ROLLING	151 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	414
Overall Diameter (mm)	1085
Static Loaded Radius (mm)	483
Rolling Circumference (mm)	3342
Rim Rec	13.0
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002711

Load capacity (Kg)

km/h / bar	3.00
10 FR	4830
25 FR	4105
30 FR	3865
40 FR	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 21:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..