

AW 708 - Data Sheet



Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer
Industrial: Trailer

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	HD	149 A8	18	AG 13.00		405	875	380	2564	TL	E11-106R-004253
400/60 - 15.5	SPECIAL	149 A8	18	AG 13.00		405	875	380	2564	TT	E11-106R-004255
400/60 - 15.5	SPECIAL	149 A8	18	AG 13.00		405	875	380	2564	TL	
400/60 - 15.5	STANDARD	136 A8	10	AG 13.00		405	875	380	2564	TL	E11-106R-003514
400/60 - 15.5	STANDARD	145 A8	14	AG 13.00		405	875	380	2564	TT	E4-106R-002712
400/60 - 15.5	STANDARD	145 A8	14	AG 13.00		405	875	380	2564	TL	E4-106R-002712
400/60 - 15.5	STANDARD	149 A8	18	AG 13.00		405	875	380	2564	TL	E4-106R-001543
400/60 - 15.5	STUBBLE RESISTANT	149 A8	18	AG 13.00		405	875	380	2564	TL	
19.0/45 - 17	STANDARD	138 A8	10	16.00		470	866	380	2536	TL	E4-106R-002334