

BK RUF N TUF - Technical Specifications



Description

BK RUF N TUF is a block pattern tire suitable for transport operations with trailers and light trucks. It is ideal for road usage and ensures excellent durability.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Light Truck • Trailer

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94014064
Ply Rating	14
Section Width (inch)	8.5
Overall Diameter (inch)	32.7
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (lbs)

mph / psi	-
-	-
-	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 23:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..