

## COMMANDER (R) - Data Sheet



### Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester • Tractor

| SIZE            | Version  | USACode  | TRA Code | LI/SS  | PR | RIM REC | RIM ALT    | SW   | OD   | SLR  | RC    | Type | TMPH | ECE             |
|-----------------|----------|----------|----------|--------|----|---------|------------|------|------|------|-------|------|------|-----------------|
| 9.5 - 20        | STANDARD | 94058921 | R1       | 105 A8 | 12 | W 8     | W 7        | 9.6  | 38.2 | 18   | 116.1 | TT   | 1    | E11-106R-005246 |
| 11.2 - 24       | STANDARD | 94054367 | R1       | 120 A8 | 12 | W 10    | W 9        | 11.6 | 44.3 | 21   | 137.1 | TT   | 0    | E11-106R-004616 |
| 12.4 - 24       | STANDARD | 94052745 | R1       | 124 A8 | 12 | W 11    | W 10       | 12.9 | 46.5 | 22.4 | 144.4 | TT   | 1    | E11-106R-004365 |
| 12.4 - 24       | STANDARD | 94057924 | R1       | 117 A8 | 8  | W 11    | W 10       | 12.9 | 46.5 | 22.4 | 144.4 | TT   | 1    | E11-106R-005208 |
| 9.5 - 24        | STANDARD | 94052912 | R1       | 110 A8 | 12 | W8      | W 7        | 9.6  | 41.9 | 20   | 130.2 | TT   | 1    | E11-106R-004364 |
| 12.4 - 28       | STANDARD | 94045846 | R1       | 121 A8 | 12 | W 11    | W 9; W 10  | 12.6 | 50.6 | 23.6 | 155.4 | TT   | 1    | E11-106R-002999 |
| 13.6 - 28       | STANDARD | 94045136 | R1       | 124 A8 | 12 | W 12    | W 11       | 14.2 | 53   | 24.5 | 160.2 | TT   | 1    | E11-106R-003002 |
| 14.9 - 28       | STANDARD | 94048021 | R1       | 130 A8 | 12 | W 13    | W 11, W 12 | 15.3 | 54.3 | 25.3 | 164.4 | TT   | 1    | E11-106R-005966 |
| 15.9 - 28       | STANDARD | 94075591 | R1       | 136 A8 | 12 | W 13    | W 11, W 12 | 15.9 | 55.5 | 0    | 0     | TT   | 0    | E11-106R-009016 |
| 16.9 - 28       | STANDARD | 94048212 | R1       | 139 A8 | 12 | W 15 L  | W 14 L     | 17.3 | 56.5 | 26.1 | 168.3 | TT   | 1    | E11-106R-003627 |
| 16.9 - 28 (21L) | STANDARD | 94075584 | R1       | 139 A8 | 12 | W 15 L  | W 14 L     | 17.3 | 56.5 | 0    | 0     | TT   | 0    | E11-106R-009015 |
| 17.9 - 28       | STANDARD | 94073214 | R1       | 140 A8 | 12 | W 15 L  | W 14 L     | 18   | 59.6 | 0    | 0     | TT   | 1    | E11-106R-007701 |
| 16.9 - 30       | STANDARD | 94067640 | R1       | 140 A8 | 12 | W 15 L  | W 14 L     | 17.3 | 58.3 | 27.1 | 178.6 | TT   | 0    | E11-106R-006618 |
| 18.4 - 30       | STANDARD | 94051502 | R1       | 145 A8 | 14 | W 16 L  |            | 18.6 | 61.6 | 28.9 | 190.3 | TT   | 1    | E11-106R-004525 |
| 18.4 - 30       | STANDARD | 94052752 | R1       | 151 A8 | 18 | W 16 L  |            | 18.6 | 61.6 | 28.9 | 190.3 | TT   | 1    | E11-106R-004368 |
| 18.4 - 30       | STANDARD | 94052844 | R1       | 151 A8 | 18 | W 16 L  |            | 18.6 | 61.6 | 28.9 | 190.3 | TL   | 1    | E11-106R-004368 |
| 18.4 - 30       | STANDARD | 94057931 | R1       | 135 A8 | 8  | W 16 L  |            | 18.6 | 61.6 | 28.9 | 190.3 | TT   | 1    | E11-106R-005247 |
| 9.5 - 36        | STANDARD | 94073566 | R1       | 122 A8 | 12 | W 8     | W 7        | 9.7  | 54.2 | 0    | 0     | TT   | 0    | E11-106R-007809 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..