

AGRIMAX RT 945 - Datenblatt



Description

AGRIMAX RT 945 wurde speziell für Reihenkulturen entwickelt: Er beschädigt die Kulturen nicht, sondern schützt die Ernte. Ferner ermöglichen seine hervorragenden Selbstreinigungseigenschaften den raschen Wechsel zwischen Feldarbeiten und Straßeneinsatz, wo AGRIMAX RT 945 brillante Leistungen zeigt. Seine robuste Karkasse verleiht dem Reifen ausgezeichnete Stabilität, erstklassige Traktion und außerordentliche Beständigkeit.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
420/90 R 30	STANDARD	94063857	R1W	147 A8/B	DW13	W 14 L	16.5	59.8	26.9	180	TL	E11-106R-006021
320/90 R 42 (12.4 R 42)	STANDARD	94038664	R1W	139 A8/B	W 10	W 9 ; W 11	12.6	64.7	29.9	194.6	TL	E4-106R-000783
320/90 R 46 (12.4 R 46)	STANDARD	94044719	R1W	146 A8/B	W 10	W 9 ; W 11	12.6	68.7	31.9	206	TL	E4-106R-001399
320/90 R 46 (12.4 R 46)	STANDARD	94051694	R1W	148 D/151 A8	W 10	W 9 ; W 11	12.6	68.7	31.9	206	TL	E11-106R-004068
380/90 R 46 (14.9 R 46)	STANDARD	94040551	R1W	155 A8/B	W 12	W 11 ; W 13	15	72.9	34.1	222.4	TL	E4-106R-00797
380/90 R 46 (14.9 R 46)	STANDARD	94021833	R1W	159 A8/B	W 12	W 11 ; W 13	15	72.9	33.8	224.4	TL	E4-106R-001409
320/90 R 50 (12.4 R 50)	STANDARD	94037612	R1W	150 A8/B	W 10	W 9 ; W 11	12.6	72.7	34.4	221.2	TL	E4-106R-000787
380/90 R 50 (14.9 R 50)	STANDARD	94037025	R1W	151 A8/B	W 12	W 11 ; W 13	15	76.9	35.7	232.3	TL	E4-106R-001487
380/90 R 50 (14.9 R 50)	STANDARD	94065479	R1W	160A8/B	W 12	W 11 ; W 13	15.4	76.9	36.3	234.6	TL	E11-106R-006446
320/90 R 54 (12.4 R 54)	STANDARD	94037094	R1W	156 A8/B	W 10	W 9 ; W 11	12.6	76.7	36.6	237	TL	E11-106R-003474
380/90 R 54 (14.9 R 54)	STANDARD	94046799	R1W	158 A8/B	W 12	W 11 ; W 13	15	80.9	37.9	245.4	TL	E4-106R-001488

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 22:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..