

AS 504 - Technische Daten



Description

AS 504 ist ein agro-industrieller Reifen, der hauptsächlich zur Bodenbearbeitung sowie zum Einsatz mit landwirtschaftlichen Geräten und zum Materialtransport entwickelt wurde. Dieser Reifen, der sich durch ausgezeichnete Selbstreinigungseigenschaften und verstärkte Haftung auszeichnet, eignet sich für Feldanhänger und Teleskoplader. Es gibt den AS 504 Reifen in verschiedenen Ausführungen, um den spezifischen Anforderungen der Endnutzer gerecht zu werden: eine „HD“-Ausführung mit besonders schnitt- und reißfester Gummimischung, während die „special“ Ausführung mit verstärkter Karkasse ein längeres Reifenleben gewährleistet.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Teleskoplader • Feld-Anhänger
Industrie: Teleskoplader

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS DRIVE WHEEL	75 A8
LI/SS FREE ROLLING	88 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	140
Overall Diameter (mm)	657
Static Loaded Radius (mm)	308
Rolling Circumference (mm)	1957
SRI (mm)	310
Rim Rec	3.50 D
Rim Alt	3.00 D ; 4.00 E ; 4 J
ECE	E4-106R-001950

Load capacity (Kg)

km/h / bar	3.50
10 FR	785
25 FR	665
30 FR	625
40 FR	560
10 DW	540
25 DW	460
30 DW	430
40 DW	385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 22:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..