

AT 316 - Datenblatt



Description

AT 316 eignet sich zum Einsatz mit kompakten Nutztraktoren für Anwendungen im Bereich Gemeindearbeiten/Wartung. Das spezielle Laufflächendesign bietet ausgezeichnete Traktion ohne dabei den Feldschutz zu beeinträchtigen – eine wesentliche Eigenschaft für Anwendungen dieser Art. Der AT 316 Reifen ist auch in Ausführung "aramid-belted" mit Aramidbändern für verstärkte Durchstichfestigkeit erhältlich.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Kompakttraktor

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 12.00 - 12	ARAMID BELTED	6	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	
24 X 12.00 - 12	STANDARD	4	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	E11-106R-004082

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 02:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..