

AW 09 - Technische Daten



Description

AW 09 wurde für die Bodenbearbeitung, die Heuernte und Transportanwendungen mit landwirtschaftlichen Geräten, Heupressen und Anhängern entwickelt. Er ist ideal für die moderne Landwirtschaft auf und abseits der Straße. Seine verstärkte Karkasse gewährleistet hohe Tragfähigkeit und ein längeres Reifenleben. AW 09 wurde mit einer speziellen, durchstichfesten Gummimischung entwickelt, die hervorragenden Widerstand gegen Stoppeln bietet.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	141 A8

Dimensions US Standard

Usa code	94037803
Section Width (inch)	11.6
Overall Diameter (inch)	33.9
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	99.2
Rim Rec	9.00
ECE	E4-106R-000376

Load capacity (lbs)

mph / psi	58
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 09:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..