

## AW 726 - Technische Daten



### Description

AW 726 wurde speziell für Anhänger bei Anwendungen zum Transport entwickelt. Er eignet sich sowohl zum Straßeneinsatz als auch abseits der Straße. AW 726 zeichnet sich durch hervorragende Performance auf der Straße und beste Selbstreinigungseigenschaften aus. Das Blockmuster gewährleistet ein langes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Anhänger

|                    |                |
|--------------------|----------------|
| Version            | ARAMID BELTED  |
| Type               | TL             |
| Tyre Size          | 11.5/80 - 15.3 |
| LI/SS DRIVE WHEEL  | 126 A8         |
| LI/SS FREE ROLLING | 139 A8         |

## Dimensions International Standard

|                            |                  |
|----------------------------|------------------|
| Ply Rating                 | 14               |
| Section Width (mm)         | 300              |
| Overall Diameter (mm)      | 855              |
| Static Loaded Radius (mm)  | 363              |
| Rolling Circumference (mm) | 2531             |
| Rim Rec                    | 9.00             |
| ECE                        | E11-106R-0010913 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 4.80 |
| 10 FR      | 3400 |
| 25 FR      | 2890 |
| 30 FR      | 2720 |
| 40 FR      | 2430 |
| 10 DW      | 2380 |
| 25 DW      | 2025 |
| 30 DW      | 1905 |
| 40 DW      | 1700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 08:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..