

BK RUF N TUF - Datenblatt



Description

BK RUF N TUF ist ein Reifen mit Blockprofil, der sich besonders für Transportarbeiten mit Anhängern und Leicht-LKWs eignet. Er ist ideal zum Straßeneinsatz und bietet ausgezeichnete Beständigkeit.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
7.50 - 16	STANDARD	8	6.00 G	5.50 F	216	830	TT	
7.50 - 16	STANDARD	12	6.00 G	5.50 F	216	830	TT	
7.50 - 16	STANDARD	14	6.00 G	5.50 F	216	830	TT	
7.50 - 16	STANDARD	16	6.00 G	5.50 F	216	830	TT	E11-54R-0015401
7.50 - 16	STANDARD	14	6.00 G	5.50 F	216	830	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 08:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..