

COLT - Technische Daten



Description

COLT ist ein Reifen mit Blockprofil, der sich für den Transport mit Anhängern und Leicht-LKWs sowohl auf dem Feld als auch auf der Straße eignet. COLT bietet verlängerte Beständigkeit und starke Leistung während des gesamten Produktlebenszyklus.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Leicht-Lkw • Anhänger

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

Dimensions International Standard

Ply Rating	12
Section Width (mm)	217
Overall Diameter (mm)	790
Rim Rec	6.00
ECE	E4-54R-0024094

Load capacity (Kg)

km/h / bar	6.00
100 LS	1385
100 LD	1315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 03:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..