

EARTHMAX SR 43 - Technische Daten



Description

Earthmax SR 43 (L-4) ist ein radialer All-Steel-Reifen, der speziell für Radlader entwickelt wurde, die in extrem felsiger Umgebung vor allem in Untertagebau zum Einsatz kommen. Der Reifen zeichnet sich durch hervorragende Leistungen bei Lade- und Transportarbeiten im Tagebau, in Steinbrüchen sowie auf Schrottplätzen aus. Das einzigartige Laufflächenmuster verleiht optimale Traktion und Stabilität. Dank seiner All-Steel-Struktur gewährleistet der robuste Earthmax SR 43 (L-4) erstklassige Stich- und Schnittfestigkeit sowie ein verlängertes Reifenleben.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	228 A2

Dimensions International Standard

Overall Width (mm)	852
Overall Diameter (mm)	1877
Static Loaded Radius (mm)	844
Rolling Circumference (mm)	5702
Rim Rec	27.00/3.5
Rim Alt	27.00/3.0; 28.00/3.5
Star Rating	***
TRA Code	L4
Tread Depth	61

Load capacity (Kg)

km/h / bar	6.50	6.75	7.00	7.25	7.50	7.75	8.00
10	26500	27250	28000	29000	30000	30750	31500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 01:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..