

LOADER PLUS - Technische Daten



Description

LOADER PLUS (L-3) ist ein speziell für Lader entworfener Diagonalreifen. Die Gummimischung der Lauffläche ist besonders schnitt- und reißfest und eignet sich bestens für Lade- und Planierarbeiten.

UM

US Standard

Construction

✚ BIAS

Machinery

Industrie: Planierer • Radlader

OTR: Planierer • Radlader

Version	DUAL BEAD
Type	TT
Tyre Size	17.5 - 25

Dimensions US Standard

Usa code	94064953
Ply Rating	20
Overall Width (inch)	17.3
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.5
Rolling Circumference (inch)	156.7
Rim Rec	14.00/1.5
TRA Code	L3
Tread Depth	33

Load capacity (lbs)

mph / psi	83
5	18200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 16:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..