

MP 567 - Technische Daten



Description

MP 567 ist ein agro-industrieller Reifen für Feld- und Straßentransport sowie Anwendungen im Bereich Gemeindearbeiten/Wartung. Es ist der perfekte Reifen für Teleskoplader und landwirtschaftliche Geräte. Der MP 567 Reifen steht für gute Traktion bei jedem Wetter sowie ausgezeichnete Selbstreinigungseigenschaften. Der Reifen bietet außerdem ein komfortables Fahrerlebnis neben einem längeren Reifenleben.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Teleskoplader
Industrie: Teleskoplader • Universelles Fahrzeug

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	325
Overall Diameter (mm)	1040
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3142
Rim Rec	11.0
Rim Alt	12 SDC
ECE	E4-54R-0022632

Load capacity (Kg)

km/h / bar	3.00
90	1850
40	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 16:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..