

MULTIMAX MP 525 - Technische Daten



Description

MULTIMAX MP 525 ist ein radialer All-Steel-Mehrzweckreifen, der für Universal- Fahrzeuge, Teleskoplader, Kompaktlader und Planierer in agroindustriellen Anwendungen entworfen wurde. Der Reifen wurde speziell entwickelt, um schwere Lasten bei höheren Geschwindigkeiten sowohl auf der Straße als auch auf dem Gelände zu tragen. Das breite, nicht laufrichtungsgebundene Profil bietet außergewöhnliche Traktion auf jeder Oberfläche und verfügt über hervorragende Selbstreinigungseigenschaften. Die starke Flanke sorgt für eine außergewöhnliche Seitenstabilität im Hebemodus und macht den Reifen zur idealen Wahl für landwirtschaftliche Arbeiten und die Materialbeförderung. MULTIMAX MP 525 weist eine einzigartige, besonders schnittfeste Laufflächenmischung auf, die dank ihrer außergewöhnlichen Widerstandsfähigkeit gegen alle Arten von Schnitten und Durchstichen für eine längere Betriebsdauer des Reifens steht.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Teleskoplader • Universelles Fahrzeug
Industrie: Kompaktlader • Planierer • Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	405/70 R 18 (15.5/70 R 18)
LI/SS	146 J/141 B/153 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1025
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3122
Rim Rec	13
Rim Alt	11; 12
ECE	E11-54R-0022030

Load capacity (Kg)

km/h / bar	3.75	4.00
100	2800	3000
50	2575	-
10	3650	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..