

## MULTIMAX MP 527 - Technische Daten



### Description

MULTIMAX MP 527 ist ein radialer Mehrzweckreifen, der speziell für Teleskoplader und Kompaktlader in agro-industriellen Anwendungen entwickelt wurde. Der Reifen weist ein Blockmuster auf, das erstklassige Traktion auch auf härtesten Oberflächen bietet. Die robuste Flanke bietet hervorragende Stabilität im Hebemodus. MULTIMAX MP 527 zeichnet sich durch eine besonders schnitt- und reißfeste Gummimischung aus, die ein langes Betriebsleben gewährleistet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Kompaktlader • Teleskoplader  
Industrie: Kompaktlader • Teleskoplader

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 500/70 R 24 IND |
| LI/SS     | 164 A8/B        |

# Dimensions International Standard

|                            |                   |
|----------------------------|-------------------|
| Section Width (mm)         | 503               |
| Overall Diameter (mm)      | 1310              |
| Static Loaded Radius (mm)  | 597               |
| Rolling Circumference (mm) | 4019              |
| SRI (mm)                   | 625               |
| Rim Rec                    | DW 16 L           |
| Rim Alt                    | DW 15 L ; DW 18 L |
| ECE                        | E4-106R-002658    |

## Load capacity (Kg)

|            |      |      |      |      |      |      |       |       |       |
|------------|------|------|------|------|------|------|-------|-------|-------|
| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0   | 4.2   | 4.4   |
| 50         | 2400 | 2850 | 3250 | 3700 | 4150 | 4450 | 5000  | -     | -     |
| 40         | 2400 | 2850 | 3250 | 3700 | 4150 | 4450 | 5000  | -     | -     |
| 30         | 2570 | 3050 | 3480 | 3960 | 4445 | 4765 | 5350  | -     | -     |
| 25         | 2665 | 3165 | 3610 | 4110 | 4610 | 4940 | 5550  | -     | -     |
| 10 Cyc.    | 2925 | 3600 | 4240 | 4875 | 5550 | 6040 | 6825  | 7200  | 7500  |
| Static     | 4485 | 5520 | 6500 | 7475 | 8510 | 9260 | 10465 | 11040 | 11500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 08:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..