

PORTMAX PT 93 - Technische Daten



Description

PORTMAX PT 93 ist ein Reifen für Terminalzugmaschinen, der speziell für den harten Dauereinsatz in Hafen- und Logistikterminals konzipiert wurde. Die spezielle antistatische Gummimischung der Lauffläche bietet außergewöhnliche Verschleißfestigkeit auch unter schwersten Einsatzbedingungen. PORTMAX PT 93 gewährleistet einen hohen Level an Manövrierbarkeit, und wartet mit erstklassigem Grip sowie verstärkter Beständigkeit auf.

UM

International Standard

Construction

RADIAL

Machinery

Industrie: Terminalzugmaschine • Anhänger

Version	INDUSTRIAL
Type	TL
Tyre Size	310/80 R 22.5
LI/SS	175 A8

Dimensions International Standard

Overall Width (mm)	308
Overall Diameter (mm)	1070
Rim Rec	9.00

Load capacity (Kg)

km/h / bar	10.00
40	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 03:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..