

RIB 324 - Datenblatt



Description

RIB 324 wurde mit einem speziellen Blockmuster der Lauffläche und einer breiten Aufstandsfläche entwickelt, um hervorragende Stabilität und Flotationseigenschaften auf lockerer Erde und Sandboden zu gewährleisten. Die robuste Nylonkarkasse und Seitenwand sowie die spezielle Gummimischung der Lauffläche stehen für erstklassige Durchstich- und Verschleißfestigkeit sowie höhere Tragfähigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Industrie: Anhänger

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
66 X 44.00 - 25	STANDARD	20	36.0 TH		1110	1700	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 02:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..