

SM 68 (GK) - Technische Daten

Description

SM 68 wurde speziell für Go-Karts entworfen. Das gleichmäßige Laufflächendesign verleiht ausgezeichnete Performance bei sportlichen Aktivitäten. Shore-Härte A 68.

UM

US Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Go-Kart



Version	STANDARD
Type	TL
Tyre Size	11 X 6.00 - 5

Dimensions US Standard

Usa code	94033409
Section Width (inch)	7.3
Overall Diameter (inch)	11.4
Rim Rec	6.75

Load capacity (lbs)

mph / psi	56
-	297

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 12:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..