

SUPER GRADER - Technische Daten



Description

SUPER GRADER (G-2) ist ein speziell für Planierer entworfener Diagonalreifen. Er bietet ausgezeichnete Traktion und hervorragende Selbstreinigung. SUPER GRADER ist aus einer speziellen Gummimischung hergestellt, die einen verlängerten Reifenlebenszyklus bietet und schweren Betriebsbedingungen Stand hält.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Planierer

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	340
Overall Diameter (mm)	1275
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3800
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2
Tread Depth	25

Load capacity (Kg)

km/h / bar	4.00
40	3240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.05.2025 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..