

SUPER SAND - Technische Daten



Description

SUPER SAND ist besonders geeignet für Anhänger, die auf sandigem Gelände bei heißem Klima im Einsatz sind. Er zeichnet sich durch hohe Flotationsfähigkeit und ist ideal für alle Arbeiten, die einen hohen Level an Manövrierbarkeit erfordern.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	16.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	415
Overall Diameter (mm)	1305
Rim Rec	10.00 W

Load capacity (Kg)

km/h / bar	2.50
50	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 07:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..