

TR 171 - Technische Daten



Description

TR 171 ist ein Reifen mit tiefer Lauffläche, der sich für Traktoren zur Bodenbearbeitung eignet. Dank der erstklassigen Selbstreinigungseigenschaften ist er ideal für nasse und feuchte Böden. Selbst unter härtesten Einsatzbedingungen bietet TR 171 mit seiner speziellen Gummimischung ausgezeichnete Traktion und außergewöhnliche Beständigkeit.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	HD
Type	TT
Tyre Size	12.4 - 24
LI/SS	120 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	315
Overall Diameter (mm)	1165
Static Loaded Radius (mm)	544
Rolling Circumference (mm)	3557
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004117
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	2.30
30	1400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 01:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..