

TR 173 - Datenblatt



Description

TR 173 ist ein Traktorenreifen, der sich bestens für feuchte Bedingungen und Reisfelder eignet. Das spezielle Laufflächenmuster bietet erstklassige Selbstreinigungseigenschaften neben reduzierter Bodenverdichtung dank einer breiten Aufstandsfläche.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
8 - 18	STANDARD	8061221	R1W	90 A8	6	W 6	W 7 ; 5.50 F	7.9	33.1	15.4	99.4	TT	E11-106R-006500
8.3 - 20	STANDARD	94066407	R1W	92 A8	6	W 7	W 6	8.3	35	16.5	106.8	TT	E11-106R-006482
8.3 - 22	STANDARD	94066414	R1W	94 A8	6	W 7	W 6	8.3	37	17.4	113	TT	E11-106R-006483
9.5 - 22	STANDARD	94066445	R1W	100 A8	6	W 8	W 7	9.5	39.3	18.6	119.9	TT	E11-106R-006485
12.4 - 24	STANDARD	94064120	R1W	111 A8	6	W 11	W 9 ; W 10	12.4	45.7	21.3	138.1	TT	E11-106R-004480
8.3 - 24	STANDARD	94066438	R1W	96 A8	6	W 7	W 6	8.3	39.2	18.4	118.5	TT	E11-106R-006484
9.5 - 24	STANDARD	94066988	R1W	102 A8	6	W 8	W 7	9.5	41.2	19.4	127.5	TT	E11-106R-006486
13.6 - 26	STANDARD	94064137	R1W	116 A8	6	W 12	W 11	13.6	49.4	23.1	149.1	TT	E11-106R-003555
14.9 - 28	HD	94067510	R1W	133 A8	12	W 13	W 11 ; W 12	15.2	53.8	24.8	165.9	TT	
14.9 - 28	STANDARD	94066902	R1W	126 A8	8	W 13	W 11 ; W 12	15.2	53.8	24.8	165.9	TT	E11-106R-006487
16.9 - 28	STANDARD	94067275	R1W	125 A8	6	W 15 L	W 14 L	17.5	57.1	26.3	175.4	TT	E11-106R-006488

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 00:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..