

TR 315 - Technische Daten



Description

TR 315 ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Gemeindearbeiten und die Bodenbearbeitung mit landwirtschaftlichen Geräten, Grabenfräsen und Obsterntemaschinen eignet. Der TR 315 Reifen hat eine breite Kontaktfläche, die ausgezeichnete Haftung und erstklassige Stabilität unter jeglichen Bedingungen neben hervorragenden Selbstreinigungseigenschaften sichert.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte •
Erntemaschine für Obst • Grabenfräse

Version	SPECIAL
Type	TL
Tyre Size	26 X 12.00 - 12

Dimensions US Standard

Usa code	94038169
Ply Rating	10
Section Width (inch)	12.1
Overall Diameter (inch)	25.8
Static Loaded Radius (inch)	11.4
Rolling Circumference (inch)	75
Rim Rec	10½ JA
Rim Alt	8½ JA ; 9½ JA
ECE	E11-106R-004519

Load capacity (lbs)

mph / psi	56
10	3195

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 09:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..