

TR 461 - Technische Daten



Description

TR 461 ist ein BKT Reifenmuster für Anwendungen im Bereich Gemeindearbeiten/Wartung mit Traktoren sowie für Ladearbeiten mit Teleskopladern. Der Flankenschutz bietet besondere Widerstandsfähigkeit gegenüber Schnitten und Quetschungen. So wird ein längeres Reifenleben auch auf harten Oberflächen neben ausgezeichneter Stabilität gewährleistet.

UM

US Standard

Construction

✚ BIAS

Machinery

Industrie: Baggerlader • Teleskoplader • Traktor

Version	STANDARD
Type	TL
Tyre Size	16.9 - 28
LI/SS	154 A8

Dimensions US Standard

Usa code	94016754
Ply Rating	14
Section Width (inch)	17.3
Overall Diameter (inch)	54.7
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	160.9
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (lbs)

mph / psi	42
25	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..