

## XL GRIP IND3 (RTG) - Technische Daten



### Description

XL GRIP (IND-3) ist ein Diagonalreifen für RTG Krane. Der Reifen weist eine robuste Karkasse auf, die aus einer speziell formulierten Gummimischung entwickelt wurde und ein verlängertes Reifenleben gewährleistet.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: RTG-Kran

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TL         |
| Tyre Size | 21.00 - 35 |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Ply Rating                 | 36        |
| Overall Width (mm)         | 580       |
| Overall Diameter (mm)      | 2020      |
| Static Loaded Radius (mm)  | 928       |
| Rolling Circumference (mm) | 5980      |
| Rim Rec                    | 15.00/3.0 |
| TRA Code                   | IND3      |

## Load capacity (Kg)

|            |       |
|------------|-------|
| km/h / bar | 9.00  |
| 10         | 31000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 01:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..