

EARTHMAX SR 32 - Technical Specifications



Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Scraper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	33.25 R 29
LI/SS	209 B

Dimensions US Standard

Usa code	94057986
TMPH	237
Overall Width (inch)	33.3
Overall Diameter (inch)	81.9
Static Loaded Radius (inch)	36
Rolling Circumference (inch)	246.1
Rim Rec	27.00/3.5
Rim Alt	26.00/3.5
Star Rating	**
TRA Code	E3
Tread Depth	68

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	33100	34200	36400	37500	38600	40800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..