

## EARTHMAX SR 42 - Data Sheet



### Description

EARTHMAX SR 42 is a radial OTR tire specially engineered for haul trains in mining and logging applications. The distinctive tread design provides outstanding traction and lateral stability as well as good braking and cornering performance on rough and gravel terrains even on ice and snow. Indeed, the special cut-and-wear-resistant tread compound is particularly suitable in extreme cold climate. EARTHMAX SR 42 features an All Steel casing for excellent durability and a long service life.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Haul Train

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
<b>14.00 R 24</b>	CUT RESISTANT COMPOUND	94067138	E4	***	171 B	10.00W	--	15	55.6	25.7	166.6	TL	48	72
<b>14.00 R 25</b>	CUT RESISTANT COMPOUND	94048984	E4	***	171 B	10.00/1.5	--	15	55.6	25.7	166.6	TL	48	72
<b>14.00 R 25</b>	CUT RESISTANT COMPOUND	94067190	E4	***	171 B	10.00/2.0	--	15	55.6	25.7	166.6	TL	48	72

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..