

EARTHMAX SR 44 - Technical Specifications



Description

EARTHMAX SR 44 is an **All Steel** radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: On/Off Truck

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 10.00 R 20 |
| LI/SS | 146/143 G |

Dimensions US Standard

| | |
|------------------------------|--------------------|
| Usa code | 94045075 |
| Ply Rating | 16 |
| Overall Width (inch) | 10.6 |
| Overall Diameter (inch) | 42.3 |
| Static Loaded Radius (inch) | 19.9 |
| Rolling Circumference (inch) | 126 |
| Rim Rec | 7.50 |
| Rim Alt | 7.0 ; 7.50VM ; 8.0 |
| ECE | E11-54R-0015908 |
| Tread Depth | 32 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 120 |
| 55 | 6600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 13:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..