

EARTHMAX SR 45 - Technical Specifications



Description

EARTHMAX SR 45 is an **All Steel** radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 is the ideal tire for all operations requiring high traction.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions International Standard

TKPH	185
Overall Width (mm)	505
Overall Diameter (mm)	1870
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5608
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4
Tread Depth	55

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..