

EARTHMAX SR 51 - Technical Specifications

Description

EARTHMAX SR 51 (L-5) is an **All Steel** radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Loader



Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	176 A2

Dimensions US Standard

Usa code	94046249
Overall Width (inch)	17.2
Overall Diameter (inch)	55
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	161.8
Rim Rec	14.00/1.5
Star Rating	*
TRA Code	L5
Tread Depth	77

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	13200	13600	14300	14800	15700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 03:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..