

EARTHMAX SR 51 - Technical Specifications



Description

EARTHMAX SR 51 (L-5) is an **All Steel** radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	195 A2

Dimensions International Standard

Overall Width (mm)	612
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	743
Rolling Circumference (mm)	4882
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L5
Tread Depth	77

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	10300	10600	11200	11500	12150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 01:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..