

EARTHMAX SR 53 - Data Sheet



Description

EARTHMAX SR 53 is an All Steel radial tire specially designed for loaders, dozers and low profile dump trucks (LPDT) operating in severe rocky conditions, including underground operations and scrap yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent traction and stability.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Dozer • Loader • Low Profile Dump Truck (LPDT)

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
17.5 R 25	CUT RESISTANT COMPOUND	L5	*	176 A2	14.00/1.5		435	1400	637	4214	TL	66
17.5 R 25	CUT RESISTANT COMPOUND	L5	**	182 A2	14.00/1.5		435	1400	637	4214	TL	66
17.5 R 25	CUT RESISTANT COMPOUND	L5	***	188 A2	14.00/1.5		435	1400	637	4214	TL	66
17.5 R 25	CUT RESISTANT COMPOUND (UMS)	L5	**		14.00/1.5		435	1400	637	4214	TL	66
20.5 R 25	CUT RESISTANT COMPOUND	L5	*	186 A2	17.00/2.0		535	1550	705	4666	TL	78
23.5 R 25	CUT RESISTANT COMPOUND	L5	*	195 A2	19.50/2.5		604	1666	758	5015	TL	84
23.5 R 25	CUT RESISTANT COMPOUND	L5	**	201 A2	19.50/2.5		604	1666	758	5015	TL	84
23.5 R 25	CUT RESISTANT COMPOUND (UMS)	L5	**		19.50/2.5		604	1666	758	5015	TL	84
26.5 R 25	CUT RESISTANT COMPOUND	L5	*	202 A2	22.00/3.0		680	1788	800	5376	TL	95
26.5 R 25	CUT RESISTANT COMPOUND	L5	**	209 A2	22.00/3.0		680	1788	800	5376	TL	95
26.5 R 25	CUT RESISTANT COMPOUND	L5	***	214 A2	22.00/3.0		680	1788	800	5376	TL	95
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	L5	**		22.00/3.0		680	1788	800	5376	TL	95
29.5 R 25	CUT RESISTANT COMPOUND	L5	*	208 A2	25.00/3.5		770	1912	859	5755	TL	103
29.5 R 25	CUT RESISTANT COMPOUND	L5	**	216 A2	25.00/3.5		770	1912	859	5755	TL	103
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	L5	**		25.00/3.5		770	1912	859	5755	TL	103
29.5 R 29	CUT RESISTANT COMPOUND	L5	**	218 A2	25.00/3.5	24.00/3.5	755	2015	905	6059	TL	102
29.5 R 29	CUT RESISTANT COMPOUND	L5	***	223 A2	25.00/3.5	24.00/3.5	755	2015	905	6059	TL	102
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	L5	**		25.00/3.5	24.00/3.5	755	2015	905	6059	TL	102
35/65 R 33	CUT RESISTANT COMPOUND	L5	**	224 A2	28.00/3.5	-	910	2063	915	6215	TL	92
35/65 R 33	CUT RESISTANT COMPOUND	L5	***	229 A2	28.00/3.5		910	2063	915	6215	TL	92
35/65 R 33	CUT RESISTANT COMPOUND (UMS)	L5	**		28.00/3.5		910	2063	915	6215	TL	92
35/65 R 33 (LPDT)	CUT RESISTANT COMPOUND (UMS)	L5	**		28.00/3.5		910	2063	915	6215	TL	92
45/65 R 39	CUT RESISTANT COMPOUND	L5	**	242 A2	36.00/4.5	32.00/4.5	1100	2577	1118	7747	TL	110
45/65 R 45	CUT RESISTANT COMPOUND	L5	**	245 A2	36.00/4.5		1125	2730	1211	8224	TL	112
45/65 R 45	CUT RESISTANT COMPOUND	L5	***	250 A2	36.00/4.5		1125	2730	1211	8224	TL	112
50/65 R 51	CUT RESISTANT COMPOUND	L5	**	253 A2	40.00/4.5		1240	3090	1371	9309	TL	128
60/80 R 57	CUT RESISTANT COMPOUND	L5	**	274 A2	47.00/5.0	47.00/6.0	1515	3930	1743	11840	TL	118

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..