

# **EM 937 IND3 (ECH) - Technical Specifications**



### **Description**

EM 937 (E-3) IND is specially designed for empty-containerhandling operations in stacking and loading applications. It features excellent durability and a long tire life. EM 937 (E-3) IND is ideal on paved surfaces and for all operations requiring a high level of handling in the port. \*For size 14.00-24 please confirm service rim or consult manufacturer/distributor

#### **UM**

**US Standard** 

#### Construction



**₩** BIAS

### Machinery

Industrial: Empty Container Handler

| Version   | PORT INDUSTRIAL |
|-----------|-----------------|
| Туре      | TL              |
| Tyre Size | 14.00 - 24      |

### **Dimensions US Standard**

| Usa code                     | 94033010 |
|------------------------------|----------|
| Ply Rating                   | 28       |
| Overall Width (inch)         | 14.8     |
| Overall Diameter (inch)      | 53.9     |
| Static Loaded Radius (inch)  | 24.7     |
| Rolling Circumference (inch) | 159.4    |
| Rim Rec                      | 10.00 W  |
| TRA Code                     | IND3     |

## Load capacity (lbs)

| mph / psi | 145   |
|-----------|-------|
| 5         | 29750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 30/04/2025 21:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..