

EM 938 - Data Sheet



Description

EM 938 has been specially designed for excavators in road construction works. The tire is made of a special tread compound, which is particularly resistant to cuts and snags, whilst the aggressive tread pattern provides excellent traction. EM 938 features outstanding self-cleaning properties. The strong casing provides extraordinary resistance to impacts and shocks even in heavy-duty operations.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Excavator

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	0	OD	SLR	RC	Type
9.00 - 20	STANDARD	E2		16	7.0	6.5 ; 7.5	256	1012	481	3070	TT
9.00 - 20	STANDARD	E2	140 B	14	7.0	6.5 ; 7.5	256	1012	481	3070	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..