

## AW 702 - Technical Specifications



### Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer  
Industrial: Trailer

Version	ARAMID BELTED
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94041725
Ply Rating	14
Section Width (inch)	11.7
Overall Diameter (inch)	33.2
Static Loaded Radius (inch)	14.6
Rolling Circumference (inch)	97.4
Rim Rec	9.00
ECE	E11-106R-004548

Load capacity (lbs)

mph / psi	69
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/05/2025 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..