

# EARTHMAX SR 51 - Technical Specifications

## Description

EARTHMAX SR 51 (L-5) is an **All Steel** radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Dozer • Loader



Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	176 A2

## Dimensions International Standard

Overall Width (mm)	437
Overall Diameter (mm)	1398
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4110
Rim Rec	14.00/1.5
Star Rating	*
TRA Code	L5
Tread Depth	61

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	6000	6150	6500	6700	7100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 02:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..